

WOOLIES

(I & C WOOLSTENHOLMES LTD)

Whitley Way, Northfields Industrial Estate, Market Deeping, Peterborough PE6 8AR
Tel : 01778 347347 Fax : 01778 341847 email: info@woolies-trim.co.uk www.woolies-trim.co.uk

AEROSOL VINYL PAINT INSTRUCTIONS



Vinyl Paint is ideal for re-colouring AND changing the colour of interior vinyls. It penetrates the surface of the vinyl, still leaving the surface pattern intact. It will not crack, peel or wear off and is highly colour fast.

It is essential that the preparatory products are used to achieve the best results, particularly e.g. where the vinyl will be expanding and contracting, such as on seats.

IMPORTANT : In an inconspicuous area please **DO A TEST PIECE BEFORE EMBARKING ON EACH PROJECT** to ensure there are no adverse reactions.

Application instructions :

1. Vinylkleen must be mixed 3 parts water to 1 part Vinylkleen, then wipe on cleaner with a clean cloth to remove dirt, then let dry before applying the primer.
2. Apply primer sparingly with cloth **DO NOT FLOOD THE VINYL**, then allow to dry.
3. Spray a thin coat of the Vinyl Paint colour onto the prepared surface. Allow to dry for approximately 10 to 15 minutes. To test the product is adhering correctly to the vinyl, place some sticky tape over the area sprayed and remove quickly. If the Vinyl Paint is present on the tape, surface penetration has not been achieved so it has not adhered correctly to the vinyl. In

this instance it may be that there is some 'foreign' substance on the vinyl which is preventing the Vinyl Paint from working correctly.

4. Vinyl Paint must be applied in light mists/coats to build up the colour. Allow 10-15 minutes between each coat to enable the product to 'flash off' before applying the next one (do not attempt to spray in one heavy coat). Between 2 and 5 mist coats evenly applied should be sufficient depending on the original colour.
5. Vinyl Paint can be handled after 20 to 30 minutes. Full curing time is 16 to 20 hours depending on temperature and humidity. Heat will reduce drying times. High humidity and damp conditions can cause poor adhesion.

THESE INSTRUCTIONS ARE BASED ON RESEARCH AND PRACTICAL EXPERIENCE.
ALTHOUGH WE HAVE EVERY CONFIDENCE IN THE PRODUCT, NO GUARANTEE CAN
BE GIVEN DUE TO THE WIDE VARIETY OF 'FOREIGN' TREATMENTS TO WHICH THE
VINYL MAY HAVE BEEN PREVIOUSLY SUBJECTED.

We stock a basic range of colours including: black, red, green, dark blue, off-white, biscuit, brown and light grey, please ask for a colour sample if you require one.

Vinyl Paint can also be colour matched to a sample but a minimum of 4 aerosols at a time must be ordered, please enquire for more details.